

混凝土料管

A4-162



应用:

■ 可用于湿态混凝土的输送作业，该作业所凭借的是混凝土泵车“重点灵活冲洗回转区域”的“高水头压力”：该产品可被用作混凝土泵输送端的排送软管。超越ASME B30.27-2009标准要求。2:1 爆破安全系数

技术参数:

- 内胶：黑色Chemi Tuf合成橡胶
- 增强层：多层高强度钢丝螺旋缠绕
- 外胶：黑色的SBR丁苯橡胶（包裹压印）
- 工作温度：-40° C到82° C(-40° F到180° F)

Applications:

■ For handling wet concrete with high head pressures at the critical flex areas of a concrete boom truck and as a discharges hose on the delivery end of high-pressure concrete pumps. Exceeds ASEM B30.27-2009. 2:1 WP to burst ratio

Technical Description:

- Inner Tube: Black Chemi Tuf synthetic rubber
- Reinforcement: Spiral high-strength steel wire
- Cover: Black SBR synthetic rubber (wrapped impression)
- Temperature Range: -40°F to 180°F (-40 C to 82 C)

混凝土料管 ALLCRETE WIRE

| 产品编码 No. | 内径 | | 外径 mm | 工作压力 bar | 弯曲半径 mm | 重量 kg/m | 包装长度 m |
|-------------|--------|-------|----------|-------------|------------|------------|-----------|
| | in | mm | | | | | |
| A4-162-2000 | 2" | 50.8 | 76.4 | 85 | 275 | 4.10 | 15.24 |
| A4-162-2500 | 2-1/2" | 63.5 | 88.9 | 85 | 300 | 4.92 | 15.24 |
| A4-162-3000 | 3" | 76.2 | 101.3 | 85 | 350 | 5.65 | 15.24 |
| A4-162-4000 | 4" | 101.6 | 127.4 | 85 | 400 | 7.29 | 15.24 |
| A4-162-5000 | 5" | 127.0 | 152.5 | 85 | 500 | 8.00 | 15.24 |

blueFuture

您身边的工业专家