

超柔软油田专用软管 A4-275



应用:

一种超柔软轻便的用于罐车及工厂内部操作的软管,可输送柴油、乙醇、汽油及含芳香剂达60%以上石油基产品。波纹型结构可以达到更小的阻力系数及超耐磨度。

技术参数:

- 内层: 黑色丁腈合成橡胶(耐油等级为A级)
- 增强层: 合成纤维多层缠绕并带有钢丝增强
- 外层: 黑色乙烯基丁腈合成橡胶(波纹状)
- 温度: -40° C至93° C

Applications:

An extremely flexible and lightweight hose for use in tank truck and drilling operation to transfer diesel, ethanol, gasoline, oil and petroleum based products. Corrugated construction for lower drag coefficient and superior abrasion resistance.

Technical description:

- Tube: Black NBR rubber RMA Class A.
- Reinforcement: Synthetic multi-layer winding and reinforced with steel wire.
- Cover: Black Buna-N-Vinyl synthetic rubber (Corrugated).
- Temperature: -40°C to 93°C.

产品编码 No.	内径		外径 mm	工作压力 bar	耐负压 in	弯曲半径 mm	重量 kg/m	包装长度 m
	in	mm						
A4-275-0750	3/4"	19	30.5	17.2	29	19.05	0.65	30.48
A4-275-1000	1"	25	36.8	17.2	29	25.40	0.81	30.48
A4-275-1500	1-1/2"	38	48.5	17.2	29	38.10	1.08	30.48
A4-275-2000	2"	51	61.8	17.2	29	50.80	1.43	30.48
A4-275-2500	2-1/2"	63	76.1	13.7	29	63.50	2.10	30.48
A4-275-3000	3"	76	88.8	13.7	29	76.20	2.51	30.48
A4-275-4000	4"	102	115.7	10.3	29	101.60	3.61	30.48
A4-275-6000	6"	152	168.4	10.3	29	146.00	6.59	30.48

blueFuture
您身边的工业专家