

清洗设备蒸汽管

A6-020



应用:

- 为处理产品和清洁设备输送蒸汽

Applications:

- Transfer of steam for processing products and cleaning equipment

技术参数:

- 内层: EPDM
- 增强层: 高强度钢丝
- 外层: EPDM、带针刺孔
- 温度: -40°C至 +208°C

Technical description:

- Inner tube: EPDM
- Reinforcement: high strength steel wire
- Cover: EPDM, with needle hole
- Temp. Range: - 40 °C to + 208 °C

清洗设备蒸汽管 EHS

产品编码 No.	内径		外径	工作压力	爆破压力	弯曲半径	重量	包装长度
	in	mm	mm	bar	bar	mm	kg/m	m
A6-020-0500	1/2"	12.7	24.0	17.2	172	70	0.49	40
A6-020-0630	5/8"	15.9	27.0	17.2	172	80	0.56	40
A6-020-0750	3/4"	19.0	32.0	17.2	172	100	0.72	40-61
A6-020-1000	1"	25.4	38.5	17.2	172	140	0.96	40-61
A6-020-1250	1-1/4"	31.8	46.0	17.2	172	200	1.27	40-61
A6-020-1500	1-1/2"	38.1	52.0	17.2	172	250	1.58	40-61
A6-020-2000	2"	50.8	67.0	17.2	172	350	2.37	40-61
A6-020-2500	2-1/2"	63.5	79.5	17.2	172	450	2.97	40-61
A6-020-3000	3"	76.2	93.0	17.2	172	550	3.88	40-61
A6-020-4000	4"	101.6	124.0	17.2	172	750	6.60	40-61

blueFuture

您身边的工业专家