

# 铂金硫化硅胶钢丝管

## A8-005



### 应用:

- 可吸入和输送用硅胶软管, 用于输送高纯度液体和化妆品; 重型应用设计。广泛应用于食品、药品和化妆品工业; 适用于在真空条件下需要大幅减少弯曲半径的应用。

### 技术参数:

- 内层: 硅胶 (Silicone), 半透明, 白色, 无臭味, 无味道, 平滑, 镜面光滑
- 加强层: 高强度多层合成纤维, 植入 AISI 304 螺旋型不锈钢线
- 外层: 硅胶 (Silicone), 半透明, 白色, 无臭味, 无味道, 平滑, 光滑表面
- 工作温度: -60°C 至 +200°C

### 适用标准:

- USP Class VI
- EU Pharmacopeia (3.1.9) 认证
- UNI EN ISO 10993
- 意大利 D.M.21/03/73 食品级认证
- 符合 FDA 标准

### Applications:

- Silicone suction and delivery hose designed for handling high purity fluids and cosmetic products. Designed for heavy-duty application. Normally used in food, pharmaceutical and cosmetic processes; particularly suitable under vacuum conditions where good mechanical resistance is required.

### Advantages:

- "Double benefit" hygienic hose: the advanced non-pigmented silicone carcass combines maximised purity with a superior mechanical strength. The accurate selection of high-purity ingredients, specific production as well as stock procedures ensure the fulfillment of Pharma grade standards according to USP Class VI.

### Technical description:

- Inner tube: Translucent silicone rubber (Silicone), clear color, odour and taste-free, smooth, mirror-like finish.
- Reinforcement: High strength synthetic textile plies, Embedded steel wire helix in SS AISI 304.
- Cover: Translucent silicone rubber (Silicone), clear color, odour and taste-free, smooth, glossy finish.
- Temperature range: -60°C up to +200°C. Sterilisation with steam at +135°C, at 3.5 bar for max 90 min.

### Standard/Approval:

- USP Class VI
- EU Pharmacopeia (3.1.9)
- UNI EN ISO 10993
- FDA Standards
- Italian D.M. 21/03/73

## 铂金硫化硅胶钢丝管 A8-005

产品编码 No.	内径		外径	工作压力	爆破压力	真空度	弯曲半径	重量	包装长度
	in.	mm	mm	bar	bar	bar	mm	mm	m
A8-008-0380	3/8"	10.0	22.0	12	36	0.9	50	0.44	20
A8-008-0500	1/2"	13.0	25.0	11	33	0.9	52	0.50	20
A8-008-0630	5/8"	16.0	29.0	10	30	0.9	60	0.57	20
A8-008-0750	3/4"	19.0	32.0	10	30	0.9	66	0.73	20
A8-008-1000	1"	25.0	38.0	9	27	0.9	86	0.92	20
A8-008-1250	1-1/4"	32.0	45.0	8	24	0.9	110	1.10	20
A8-008-1500	1-1/2"	38.0	52.0	7	21	0.9	130	1.40	20
A8-008-2000	2"	51.0	65.0	6	18	0.9	200	1.80	20
A8-008-2500	2-1/2"	63.5	77.5	5	15	0.9	250	2.41	20
A8-008-3000	3"	76.0	90.0	4	12	0.9	350	2.82	20

blueFuture

您身边的工业专家