

## 耐真空光滑特氟龙软管 AX-005



### 优点:

- 口径: 1/2" 到 2", 符合 DIN 26055
- 温度范围: -70°C 至 +260°C
- 标准与防静电内衬可供选择, 通过 ATEX 认证
- 内壁平滑的 PTFE 软管, 内置不锈钢螺旋钢丝加强, 外覆 SS304 不锈钢编织
- 柔韧性高, 抗扭结, 即使在高温时都有极好的耐高压和耐真空性能, 符合 FDA 和 USP 认证
- 特别适用于粘性介质的输送, 动态工况及对清洁要求很高的场合

### Advantages:

- Range 1/2"-2" (DN12-DN50) hose in accordance to DIN 26055.
- Virgin and anti-static liners available, ATEX Certified
- Non-convoluted, ultra hygienic flexible PTFE liner with external embedded stainless steel vacuum spiral and 304 stainless steel over braid as standard.
- Excellent vacuum and pressure ratings, even at elevated temperatures

### Applications:

- Choose when dynamic endurance, product viscosity, contamination hazard, turbulence, flow rate and hygienic clean ability are areas of particular concern.

## 耐真空光滑特氟龙软管 AX-005

产品编码 No.	Size in.	内径 mm	外径 mm	内衬壁厚 mm	工作压力 bar	爆破压力 bar	弯曲半径 mm	重量 kg/m
AX-005-0500	1/2"	11.5	15.8	1.25	50	250	38	0.29
AX-005-0630	5/8"	15.5	20.5	1.25	50	250	42	0.36
AX-005-0750	3/4"	18.5	23.6	1.00	60	290	50	0.43
AX-005-1000	1"	22.8	27.7	1.00	40	210	70	0.65
AX-005-1250	1-1/4"	30.5	36.8	1.50	45	210	85	0.75
AX-005-1500	1-1/2"	36.5	43.1	1.50	40	175	100	0.80
AX-005-2000	2"	48.5	55.2	1.65	25	135	140	0.95

防静电软管可供选择

blueFuture

您身边的工业专家