

化学品排吸管 PLUNKETT U A5-006



应用:

- UPE超高分子量聚乙烯内层设计,耐化学品腐蚀,可广泛应用输送石油化工、锂电池、精细化工、原料药、化妆品等行业的化学溶剂物料。

技术参数:

- 内层:食品级高分子量聚乙烯(UPE)材质,白色,光滑
- 增强层:高强度合成线绳,内置螺旋钢丝加强
- 外层:耐老化、耐臭氧、耐腐蚀 EPDM 合成橡胶,绿色,表面波纹
- 工作温度: -40°C至 +93°C

适用标准:

- FDA 21,CFR 177.1520

Applications:

- UPE ultra-high molecular weight polyethylene inner layer design, resistant to chemical corrosion, can be widely used to transport chemical solvent materials in petrochemical, lithium batteries, fine chemicals, raw materials, cosmetics and other industries.

Technical description:

- Inner tube: white, smooth, ultra high molecular weight polyethylene
- Reinforcement: high strength synthetic cord and helix wire
- Cover: green, corrugated, EPDM rubber, resistant to chemical, weathering and ozone
- Temperature range: - 40 °C to + 93 °C

Standard/Approval:

- FDA 21, CFR 177. 1520

化学品排吸管

PLUNKETT U

产品编码 No.	内径 in mm	外径 mm	工作压力 bar	爆破压力 bar	耐负压 bar	包装长度 m	
PLUNKETT U-0500	1/2"	12.7	24.5	10	40	0.9	60
PLUNKETT U-0750	3/4"	19.1	31	10	40	0.9	60
PLUNKETT U-1000	1"	25.4	37	10	40	0.9	60
PLUNKETT U-1250	1-1/4"	31.8	44	10	40	0.9	60
PLUNKETT U-1500	1-1/2"	38.1	51	10	40	0.9	60
PLUNKETT U-2000	2"	50.8	67	10	40	0.9	60
PLUNKETT U-2500	2-1/2"	63.5	79	10	40	0.9	60
PLUNKETT U-3000	3"	76.2	92	10	40	0.9	60
PLUNKETT U-4000	4"	101.6	118	10	40	0.9	60
PLUNKETT U-5000	5"	125.0	147	10	40	0.9	30
PLUNKETT U-6000	6"	152.4	175	10	40	0.9	30

