

化学品排吸管HODUR

A5-007



应用:

- 优异的化学耐性，适用于绝大多数的腐蚀性化学品。广泛用于化工、锂电池、精细化工、原料药及相关行业各种化学品生产和运输过程中的压力，自重或吸排使用。

优点:

- 良好的耐腐蚀性能，用于绝大多数的化学物质
- 波纹状外壁保证了更好的柔性
- 具有良好的弯曲半径
- 具有优秀的耐老化，耐候，及耐臭氧性能
- 耐温性能好
- 具有优异的耐磨损性能

技术参数:

- 内胶：超高分子量聚乙烯(UHMWPE)
- 增强层：多层合成纤维螺旋缠绕并带有2根螺旋钢丝
- 外胶：蓝色三元乙丙合成橡胶，表面波纹
- 工作温度：-40°C 至 +100°C

Applications:

- Excellent chemical resistance, suitable for most corrosive chemicals. It is widely used for pressure, self-weight or suction discharge in the production and transportation of various chemicals in chemical industry, lithium battery, fine chemical industry, API and related industries.

Advantages:

- Very good corrosion resistance, a versatile hose for a wide range of chemicals
- Corrugated cover with good flexibility
- Good mechanical strength and excellent bending radius
- Good resistance to ageing, atmospheric conditions and ozone
- High temperature resistance
- Good abrasion resistance hose cover

Technical description:

- Tube: Ultra-High Molecular Weight Polyethylene (UHMWPE)
- Reinforcement: Spiral-plyed synthetic fabric with double wire helix
- Cover: Blue EPDM synthetic rubber, corrugated (wrapped cover)
- Temperature range: -40°C to +100°C

化学品排吸管 HODUR

产品编码 No.	内径		外径 mm	工作压力 bar	爆破压力 bar	耐负压 bar	弯曲半径 mm	重量 kg/m	包装长度 m
	in	mm							
HODUR-0500	1/2"	12.7	24.1	13.8	52	0.9	76	0.49	60.96
HODUR-0750	3/4"	19.1	31.0	13.8	52	0.9	89	0.68	60.96
HODUR-1000	1"	25.4	37.3	13.8	52	0.9	102	0.89	60.96
HODUR-1250	1-1/4"	31.8	43.9	13.8	52	0.9	102	1.09	60.96
HODUR-1500	1-1/2"	38.1	50.0	13.8	52	0.9	127	1.25	60.96
HODUR-2000	2"	50.8	64.8	13.8	52	0.9	152	1.82	60.96
HODUR-2500	2-1/2"	63.5	79.8	13.8	52	0.9	203	2.65	60.96
HODUR-3000	3"	76.2	92.2	13.8	52	0.9	229	3.14	60.96
HODUR-4000	4"	101.6	118.6	13.8	52	0.9	254	4.18	60.96
HODUR-6000	6"	152.4	175.0	13.8	52	0.9	457	8.90	30.48

