

钢丝真空管TS型

PX-019



应用:

- 抗折弯、折弯压扁性强，流体不易停止，安全可靠
- 耐油性优异，胶管不易硬化，使用寿命长
- 透明度高，可确认流体，安全放心
- 符合RoHS2修正规制，安全放心

技术参数:

- 主材质: 软质聚氯乙烯
- 加强材料: 硬钢丝
- 颜色: 天然透明带图案条
- 包装: TS-6~25: 筒卷 TS-32~100: 薄膜卷
- 工作温度: -5°C至+60°C

优点:

- 透明
- 耐油
- 防折弯、压扁
- 泵送、吸引用

Applications:

- Strong resistance to bending and flattening, the fluid is not easy to stop, safe and reliable
- Excellent oil resistance, the hose is not easy to harden, long service life
- High transparency, fluid can be confirmed, safe and secure
- Comply with RoHS2 revised regulations, safe and secure

Technical description:

- Main material: soft polyvinyl chloride
- Reinforcing material: hard steel wire
- Color: natural transparent strip with pattern
- Packing: TS-6-25: Reel TS-32-100: Film reel
- Working temperature: -5 C to +60 C

Advantages:

- Transparent
- Oil resistant
- Anti-bending and flattening
- For pumping and suction

钢丝真空管TS型

PX-019

产品编码 No.	内径 in	mm	外径 mm	使用压力 Mpa	标准长度重量 kg/卷	标准长度 m	最小弯曲半径 mm
PX-019-6	1/4"	6	11	-0.1~0.8	11	100	25
PX-019-8	5/16"	8	13.5	-0.1~0.8	14	100	35
PX-019-9	3/8"	9	15	-0.1~0.8	17	100	40
PX-019-12	1/2"	12	18	-0.1~0.5	23	100	50
PX-019-15	5/8"	15	22	-0.1~0.5	32	100	60
PX-019-19	3/4"	19	26	-0.1~0.4	21	50	80
PX-019-25	1"	25	33	-0.1~0.4	27	50	100
PX-019-32	1-1/4"	32	41	-0.1~0.3	31	40	130
PX-019-38	1-1/2"	38	48	-0.1~0.3	39	40	150
PX-019-45	1-3/4"	45	56	-0.1~0.3	55	40	189
PX-019-50	2"	50	62	-0.1~0.3	60	40	200
PX-019-63	2-1/2"	63	80	-0.1~0.2	54	20	265
PX-019-75	3"	75	92	-0.1~0.2	62	20	310
PX-019-90	3-1/2"	90	108	-0.1~0.2	44	10	370
PX-019-100	4"	100	118	-0.1~0.2	48	10	410

