

## 水气多用途软管WAS EPDM

A0-004

VELON® WAS EPDM NON-CONDUCTIVE 1"(25.4mm) 300PSI W

### 应用:

- 用于一般工业应用, 适用于空气、水、油等不同场合, 不适合输送化学品或者磨损性介质

### Applications:

- For general industrial transferring of air, water, oil, not suitable for chemicals or abrasion medium

### 技术参数:

- 内层: 黑色EPDM合成橡胶, 光滑, 绝缘不导电
- 增强层: 高强度合成线绳
- 外层: 红/蓝/黄/黑/绿色可选, EPDM合成橡胶, 光滑, 耐风化
- 耐臭氧工作温度: -40°C至+100°C

### Technical description:

- Inner Tube: EPDM synthetic rubber, black, smooth
- Reinforcement: High strength synthetic cord
- Cover: Abrasion-resistant EPDM synthetic rubber, the colors black, red, blue, green, yellow are available
- Working temperature: -40 °C to +100 °C

产品编码 No.	内径 in. mm	外径 mm	工作压力 bar	爆破压力 bar	包装长度 m	
WAS EPDM-0190	3/16"	4.8	12	20.7	62	100
WAS EPDM-0250	1/4"	6.4	13	20.7	62	100
WAS EPDM-0310	5/16"	7.9	15	20.7	62	100
WAS EPDM-0380	3/8"	9.5	17	20.7	62	100
WAS EPDM-0500	1/2"	12.7	21	20.7	62	100
WAS EPDM-0630	5/8"	15.9	26	20.7	62	100
WAS EPDM-0750	3/4"	19.1	29	20.7	62	100
WAS EPDM-1000	1"	25.4	36	20.7	62	100
WAS EPDM-1250	1-1/4"	31.8	44	20.7	62	30
WAS EPDM-1500	1-1/2"	38.1	54	20.7	62	30
WAS EPDM-2000	2"	50.8	66	20.7	62	30

